

Features


- ▶ Plug can directly be inserted into a socket without pulling back the sleeve of the socket.
- ► Since an outer diameter of the coupler plug is sealed with the O-ring, there is no air leak, even in the case of a small cut at the end of the plug.
- ▶ Hybrid Couplings use a heat treated sleeve to improve the product's lifecycle.



	S (SOCKET)						
	SH Type						
	Model			Dimension	ons (mm)		
	Model	ND	L	NL	D	Hex	Weight(g)
	SH20-HB	9	69	28	26	20	85
	SH30-HB	10.9	73	32	26	20	87
	SH40-HB	13.7	73	32	26	20	90



	S (SOCKET)						
SM Type							
	Model			Dimension	ons (mm)		
		Т	L	TL	D	Hex	Weight(g)
	SM20-HB	PT1/4"	54	13	26	20	85
	SM30-HB	PT3/8"	55	14	26	20	91
	SM40-HB	PT1/2"	55	15	26	22	104



ı	S (SUCKET)								
ı	SF Type								
	Model			Dimension	ons (mm)				
	Model	Т	L	TL	D	Hex	Weight(g)		
	SF20-HB	PT1/4"	52	12	26	19	88		
	SF30-HB	PT3/8"	55	14	26	21	101		
	SF40-HB	PT1/2"	56	15	26	27	130		



P (PLUG)						
PH Type						
Туре	Model	Hose Size				
	PH-20	5/16" HOSE				
PH-TYPE	PH-30	3/8" HOSE				
	PH-40	1/2" HOSE				




P (PLUG)						
PM Type						
Model	Thread Size					
PM-20	PT 1/4"					
PM-30	PT 3/8"					
PM-40	PT 1/2"					
	PM Type Model PM-20 PM-30					




P (PLUG)						
PF Type						
Type	Model	Thread Size				
	PF-20	PT 1/4"				
PF-TYPE	PF-30	PT 3/8"				
	PF-40	PT 1/2"				

HYBRID COIL HOSE COUPLER





Model			Dimension	ons (mm)		
Model	ND	L	D	Hex-1	Hex-2	Weight(g)
KCH-08HBS	HOSE 8PIE	61.3	14	26	19	67
KCH-10HBS	HOSE 10PIE	62.8	17	26	19	70
KCH-12HBS	HOSE 12PIE	62.8	19	26	19	76



		Dimensions (mm)					
Model	ND	L	Hex-1	Hex-2	Weight(g)		
КСН-08НВР	HOSE 8PIE	49	14	14	34		
KCH-10HBP	HOSE 10PIE	50.5	16	17	40		
KCH-12HBP	HOSE 12PIE	50.5	17	19	50		

CO₂ & ARGON COUPLER

PT 3/8" 5/16" HOSE



SM-500AR

TSH-500AR



	Model	Thread and Hose Size
	PF-500AR	9/16 x 18 UNF
	PM-500AR	PT 1/4"
	PH-500AR	5/16" HOSE