



TYPE	0.5	1.0	2.0	4.0	6.0	8.0	13	16	19
TORQUE(kg-m)	0.5	1.0	2.0	4.5	6	8	13	16	19
CAPACITY(W, 20°C)	11	15	20	25	30	35	40	45	55
GAP	0.3	0.3	0.3	0.5	0.5	0.5	0.5	0.5	0.5
HUB dH7	12	15	20	25	30	30	30	40	40
KEY bE9 X h	4X13.8	5X17.3	5X22.3	7X28.3	7X33.3	7X33	7X33.3	10X43.3	10X43.3
A	63	80	100	125	137	160	180	200	216
B	68	85	106	133	146	169	190	213	229
D	80	100	125	150	165	190	210	230	270
E	72	90	112	137	150	175	195	215	245
F	35	42	52	62	65	80	106	100	130
G	30	35	44	49	65	65	65	83	83
H	22	24	27	30	31	33	38	40	50
I	2	2	3	4	4	4	5	5	6
K	24	27	30	33	35	37	42	44	55
L	43.3	51.3	63.3	69.5	76.5	83.5	96.5	101.5	116.5
M	10	14	20	22	24	27	30	33	34
N	M4X120°	M5X120°	M5X120°	M6X120°	M8X120°	M8X120°	M8X120°	M10X120°	M10X120°
P	15	20	27	30	34	38	44	47	50
Q	5	5	7	7	7	9	9.5	9.5	10.5

Example

